



December 3-6, 2007, Santa Clara Marriott, Santa Clara, CA

Exposing open-source Nagios plug-ins thru CIM

Rodolfo Kohn, Intel

Sebastian Ganame, Nexius



Disclaimer

- The information in this presentation is part of a work in progress
- This information is subject to change

Agenda

- Nagios^{*}
 - Architecture
 - Plug-ins characteristics
- Nagios-CIM^{*} Solution
 - Nagios-CIM integration
 - Nagios plug-ins thru CIM
 - Proposed framework
 - Indication Provider Implementation
- Demo
- Conclusions and future work










Why Nagios?

- Among the most used open-source monitoring tools
- Open and pretty simple plug-in based architecture
- Massive plug-in developers community
 - Enabling other management tools/frameworks to use these plug-ins thru a standard interface looks appealing
 - Nagios community plug-ins:
www.nagiosexchange.org

Nagios console

- This is the high-level view of a host services status in Nagios Web page:

Service Status Details For All Hosts

Host 	Service 	Status 	Last Check 	Duration 	Attempt 	Status Information
fswin-1	NRPE-Test	CRITICAL	11-24-2007 10:00:12	0d 0h 8m 17s	1/3	CHECK_NRPE: Socket timeout after 10 seconds.
	Oracle Connections	CRITICAL	11-24-2007 10:01:09	0d 0h 7m 20s	1/3	CHECK_NRPE: Socket timeout after 10 seconds.
	PING	CRITICAL	11-24-2007 10:07:06	0d 0h 6m 23s	1/4	PING CRITICAL - Packet loss = 100%
	Sites Deviation	CRITICAL	11-24-2007 10:03:03	0d 0h 5m 26s	1/3	CHECK_NRPE: Socket timeout after 10 seconds.
localhost	Current Load	OK	11-24-2007 10:07:01	22d 18h 6m 40s	1/4	OK - load average: 4.79, 2.02, 0.77
	Current Users	OK	11-24-2007 10:07:58	57d 18h 42m 45s	1/4	USERS OK - 2 users currently logged in
	HTTP	 WARNING	11-22-2007 17:04:29	26d 3h 32m 30s	4/4	HTTP WARNING: HTTP/1.1 403 Forbidden
	MYSQLD	 CRITICAL	11-24-2007 10:00:41	8d 18h 54m 6s	4/4	CRITICAL ERROR - Unable to connect to database " on server '127.0.0.1'
	PING	OK	11-24-2007 10:06:38	57d 18h 41m 30s	1/4	PING OK - Packet loss = 0%, RTA = 0.52 ms
	Root Partition	OK	11-24-2007 10:07:34	1d 17h 12m 19s	1/4	DISK OK - free space: / 3685 MB (50% inode=84%):
	SSH	 OK	11-22-2007 17:07:07	22d 20h 25m 56s	1/4	SSH OK - OpenSSH_4.4 (protocol 1.99)
	Swap Usage	OK	11-22-2007 17:08:04	51d 19h 50m 1s	1/4	SWAP OK - 100% free (501 MB out of 501 MB)
	Total Processes	OK	11-22-2007 17:09:01	51d 19h 49m 23s	1/4	PROCS OK: 62 processes with STATE = RSZDT


Nagios architecture

• 3 core building blocks:

- Core engine
 - components definition
 - orchestration
- Add-ons
 - firewalls bypassing
 - NSCA
 - NRPE
 - DB historical data
- Plug-ins
 - measuring work

Indirect Host Checks

Last Updated: 07-12-2001



[Picture Source: Nagios 3.0 online Documentation]

Nagios plug-ins

- Nagios acquires measurements only through plug-ins
- Almost anything that can generate output to the STDOUT is a potential Nagios plug-in
 - Required: **OK** | **WARNING** | **CRITICAL**
 - Optional: Raw Data – Statistical data
- Its output depends on received parameters
- The Nagios core engine is agnostic to the type and semantics of the reported metric

Nagios plug-ins distribution

- Some of them comes with Nagios official distribution
 - Examples: `check_http`, `check_disk`, `check_mem`, ...
- A huge percentage of them are developed by the community for a wide range of resources monitoring, including special hardware as well as very unusual uses
 - `check_dell_sensors` (Dell* chassis)
 - `oracle_writeaccess`
 - `check_pcoweb` (air conditioning)
 - 100+ for SNMP usage
 - 50+ for Windows monitoring thru NT NRPE version
 - ...


Nagios-CIM integration

- Two aspects
 - Seamless utilization of Nagios plug-ins thru CIM
 - Utilization of CIM by Nagios
- This work is focused on plug-ins utilization thru CIM

Nagios plug-ins thru CIM

- Nagios plug-ins can be used to implement specific providers
 - Indication Providers (Alert indications)
 - Property Providers
 - Certain properties population in Instance Providers
- Different design approaches
- Plug-in usage should be seamless
- The provider-CIMOM interface should be CMPI

Nagios plug-ins thru CIM diagram




Nagios plug-ins considerations

- A plug-in can provide different information
 - Depending on the options and arguments passed
- A plug-in can be concurrently run by different providers
 - Possibility of race conditions in some plug-ins
- A plug-in is executed in a periodic basis
- Configuration must take place before plug-in usage
- Dynamic management of plug-ins is desirable


Proposed framework

- The framework allows an easy and straightaway method for using third-party plug-ins
- A script finds all plug-ins and asks the operator to enter the required configuration values for each plug-in
- The configuration data is stored in the CIM repository
 - Specific extension schema has been created for Nagios plug-ins
- A general Nagios plug-in indication provider has been designed to execute all Nagios plug-ins
- When a subscription is received the indication provider reads the configuration data for each plug-in and executes it
- For properties, the provider searches the appropriate plugin functionality for the class/property

Schema diagram




Class hierarchy




Nagios plug-in indication provider implementation

- Subscription for Alert Indications is received
- One or more plug-ins are executed depending on the filter
- Available plug-ins information is read from the repository
- For each plug-in/args one thread is created
- Each plug-in/args generates a unique indication



Demo

- There are 6 Nagios plug-ins for monitoring:
 - check_procs: process processor-time usage (Nagios distribution)
 - check_disk: disk status (Nagios distribution)
 - check_users: users in the system (Nagios distribution)
 - check_xen: Xen domains (Nagiosexchange web site)
 - check_system_pp: services up in the system (Nagiosexchange web site)
 - check_my_test: random value (developed)
- The plug-ins are configured in a configuration file 
- A script reads the configuration file and creates the appropriate instances and associations in the repository
- A client console creates a CIM subscription for all AlertIndications
- The Indication Provider creates one thread per plug-in
- Each plug-in is executed in a periodic basis with the configured arguments
- For each plug-in, the associated indication is published if the execution output is Warning or Critical
- The client displays the indications received

Configuration

Subscription

Working

Demo

Conclusions

- This work enables any CIM-compliant management software to seamlessly use all existing Nagios plug-ins for indication-based monitoring and property querying
- The proposed framework provides a simple and fast procedure to configure and enable Nagios plug-ins
- It sets the basis of a CIM profile for reusing already existing monitoring plug-ins thru CIM

Future work

- To implement indications delivery for dynamic thresholds (ThresholdIndication)
- To implement the solution for property provider
- To modify or extend Nagios core engine as to use CIM as the standard for modeling and accessing managed assets
- This work could contribute to a future profile for exposing third-party monitoring plug-ins thru CIM

Questions & Answers



Legal notices

Intel, Intel logo, and Intel. Leap ahead. logo are trademarks of Intel Corporation in the U.S. and other countries.

Nexius and Nexius Wireless logo are trademarks of Nexius Wireless Co.

*Other names and brands may be claimed as the property of others.

Backup slides

- The core engine is basically in charge of the orchestration of the monitoring
 - Triggers the measurement polling
 - Processes the measurements that are pushed by the monitored services
 - Generates alerts/notifications/reactions based on service status
- Uses the Add-ons for avoiding firewalls
 - NRPE (Nagios Remote Plug-in Executor)
 - NSCA (Nagios Service Check Acceptor)

Plug-in configuration

```
[PLUGIN]
```

```
Name=check_procs
```

```
Optargs="-w 20 -c 50 --metric=CPU"
```

```
Functionality="Check processes processor usage"
```

```
SWElemID=1
```

```
Mode=Indication
```

```
FunctionalityInstanceID=check_procs_001
```

```
IndicationID=0xFFEF0091
```

```
ProbableCause="Process consuming too much CPU"
```

```
Frequency=5
```

```
SourceClass=CIM_Process
```

